

Ref: CW/RNS/LT/31072016

Date: 07-08-16

MANAGING DIRECTOR RENAISSANCE APPARELS Ltd Nawjor, Islampur Road, Konabari, Gazipur

Sub: Offer for supply, installation of LT PANEL

SL#	Descriptions	Qty	Unit	Unit price	Total price
				IN TAKA	IN TAKA

01) EXISTING DB MODIFICATION &AUTO CHANGEOVER FOR EXISTING GENERATOR: Sets 401,125.00 401,125.00

-Cost of component for LT Swiitchgear as per attached technical specifications.

02) LOADING, UNLOADING, TRANSPORTATION

20,000.00

20,000.00

(Cost of complete of the above without any cable & civil works)

Total Price

421,125.00

TERMS & CONDITIONS:

01) Validity: Our offer will remain valid for a period of 30 days from the date of this offer.

02) Delivery: Within 60 days after receipt of confirmed order & payment asper clause # 3.

03) Payment: 50% Cash/PO/DD alongwith order & remaining 50% after pre-delivery inspection & before delivery of goods.

04) Fabrication

& assembly: Fabrication & assembly will be done at our factory.

Thanking you.

TYours very truly, Cross World Power Ltd.

Engr. Mohibul Hoque Sr. Manager Sales

Cell: 01755514773

Engineer, Sales

Cell: 01755514748



TECHNICAL SPECIFICATIONS

01) LT SWITCHGEAR Panel: 1 Set

Sheet steel fabricated, floor mounting, tropicalized design, indoor type, low tension switchgear for 3 phase, 4 wire, 50 Hz,380/415V AC system & shall be supplied complete TPN busbars suitably sized & properly insulated arrange to withstand & short current of 50KA for 1 sec. The boards are designed & constructed in accordance with

BS5486/IEC439.

Busbars and other live parts are spaced and insulated in accordance with European standards IEC158,UTE C 20 -040, VDE - C 110 for 660V.

All ACB/MCCB units & panel boards shall fully comply regulations of the 15th edition IEE wiring regulation for isolation and switching.

This panel shall comprise of:

Incoming:

- 400A, TP, 36KA, 415V,50 Hz, MCCB with adjustable overcurrent and short circuit protection Brand: ABB, Italy
- 400A Magnetic Contactor Brand: ABB
- 3 Current transformer: 400/5A
- Digital Ammeter scaled (0-400A) with selector switch 1
- Digital Voltmeter scaled (0-500V) with selector switch 1
- Phase indicator RED/YELLOW/BLUE. 6
- 6A,TP,MCB for control Circuit.
- 2 ON/OFF Push button
- Fan with dust filter
- Set Bottom plate with cable gland 1
- Set Busbar insulation tube 1
- Electrical Interlock

Outgoing:

Breakers will be supplied by Customer

Suitably size TPN+1/2E Copper Busbar & enclosure