GOVERNMENT OF PEOPLE'S REPUBLIC OF BANGLADESH

College Education Development Project (CEDP) Lalmatia Mohila College, Lalmatia, Dhaka-1207

Cross World Power Ltd. House No- 1/B, Road No. 90, Gulshan-2 Dhaka-1212, Bangladesh

Subject: Notification of Award (NOA).

i) lmc/cedp/idg/otm/goods/g-7; Issued on: 14/01/2021

ii) Invitation for Tender No.: 3; Package No.: G-7

This is to notify you that your Tender dated 28/01/2021 for the supply of Goods and related Services for procurement of 250 KVA Diesel Generator for the Contract Price of BDT. 31,45,000.00 (Taka Thirty One Lac Forty Five Thousand) as corrected and modified in accordance with the Instructions to Tenderers, has been approved by the competent authority.

You are thus requested to take following actions:

accept in writing the Notification of Award within seven (7) working days of i. its issuance pursuant to ITT Sub-Clause 61.3

furnish a Performance Security in the specified format and in the amount of ii. Tk BDT. 3,14,500.00 (Taka Three Lac Fourteen Thousand Five Hundred Only) ,within fourteen (14) days of receipt of this Notification of Award but not later than 05/04/2021, in accordance with ITT Clause 63.2

sign the Contract within twenty-eight (28) days of issuance of this iii. Notification of Award but not later than 12/04/2021, in accordance with ITT Clause 66.2

You may proceed with the execution of the supply of Goods and related Services only upon completion of the above tasks. You may also please note that this Notification of Award shall constitute the formation of this Contract, which shall become binding upon you.

We attach the draft Contract and all other documents for your perusal and signature.

(Arc 100)20 Professor Dr. Md. Rafiqul Islam

Principal and IDG Manager Professor Dr. Md. Rafiqui Islam

Lalmatia Mohila College

Lalmatia, Dhaka-1207 Farel Co

Principal Lalmatia Mohila College

Lalmatia, Dhaka-1207.

CROSS WORLD POWER LIMITED
BOQ OF 250kVA GENERATOR
CLIENT - LALMATIA WOMEN COLI

		Cross-world
SKVA GENERATOR		
LMATIA WOMEN COLLEGE	ADDRESS- LALMATIA, DHAKA	DATE-21.1.2021
OB DESCRIPTION TECHNICAL DETAILS / RRAND	SCOPE OF LION OTY UNIT TOTAL BAT	TE RENADRYS
	003 A	つけることのこと

Electrical System: A11C -1857m NYY Do To ATS A21C -1287m NYY Do To ATS A21C -1287m NYY ATS TO LOAD 1 A21C -1287m NY ATS TO LOAD 1 A21C -12								
Electrical System: AXIC-185rm NVY MAINS To ATS	NO F	JOB DESCRIPTION	TECHNICAL DETAILS/ BRAND	SCOPE OF	MOU		QTY	QTY RATE
AXIC - 185rm NYY DOT TO ATS AXIC - 185rm NYY ATS TO LOAD 1 AXIC - 25rm NYY ATS TO LOAD 1 AXIC - 25rm NYY ATS TO LOAD 1 AXIC - 25rm NYY ATS TO LOAD 2 AXIC		ectrical System:						
Power Cable (35 °C Ambient on Air) AXIC - 25 rm NYY MAINS To Air S AXIC - 25 rm NYY ATS TO LOAD 1 AXIC - 25 rm NYY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATS TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO LOAD 2 AXIC - 25 rm NY ATT TO	4		4X1C -185rm NYY DG To ATS		Meter		55	
Power Cable Lugs 2007 10 Cable For Sensing 200 Feet 200 Cable For Sensing 200 Feet 200 Cable For Sensing 200 Feet 2	1.1 Pov	wer Cable (35 °C Ambient on Air)	4X1C -130rm NYY MAINS TO ATS		Meter		15	15 2,227 7 1 450
25 rm Material - Copper Surface-Electro Tinned	-		4X1C -25rm NYY ATS To LOAD 2		Meter	\neg	7	
Control cable For ensing	1 7 00		185 rm Material -Copper, Surface-Electro Tinned		Pcs	\top	18	
Control cable For Sensing			25 rm Material - Copper , Surface-Electro Tinned		Pcs	$\overline{}$	0	6 18
PoyC Flexible pipe 4"6 local	1.3 Cor	ntrol cable For Sensing	4 X 1.2 rm (40/0.19 mm)Flexible Cable		Meter		31	
Royal Plug & Screw 1.5" length PVC Tape Royal Bolt PVC Tape Royal Bolt Royal		C Flexible pipe	4"Ø local		Meter		20	<i>(</i> 1)
Royal Plug & Screw PVC Tape Note Tap	1.5 Sad	ddle for flexible pipe	4" dia local		Pcs		20	
PNC Tape PNC Tape Adhesive Tape 04 color (Red/Yellow/Black/Blue)		yal Plug & Screw	1.5" length		Pack		2	
Royal Bolt Cable Laying Charge Cable Laying System Carthing System Earthing Boring Earthing Boring Earthing Boring Earthing Boring Earthing Boring Earthing Boring Earthing Copper Lead Earthing Boring Earthing Boring Earthing Copper Lead Earth cable lugs Earth cable lugs Earth cable lugs Exhaust System: Exhaust System: Exhaust System: Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Flange Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Flange Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Flange Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Flange Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Silencer Straight Pipe with Glasswool (25.4mm min thickness) Exhaust Silencer Straight Pipe Exhaust Silencer Straight Pipe Cooling System: Exhaust Silencer Straight Pipe Exhaust Silencer Straight Pipe Exhaust Silencer St	1.7 PV0	CTape ~	Adhesive Tape 04 color (Red/Yellow/Black/Blue)		Pcs		12	
Reyal Bolt Cable Itaying Charge Charg	1.8 PIB	Tape			Pcs	- 1	1	_
Cable Laying Charge L - 10" Earthing System Cable laying & termination of 185 rm Earthing Boring 100 feet GI Pipe 38 mm Earthing Copper Lead 2 SWG for Boring & Termination Earthing Block / Equipotential bar 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Block / Equipotential bar AM SPipe bore S', thickness 3-4mm Exhaust Flange Long radius 90 deg Low S' Harm Exhaust Flange Low File Bow S' Bore Exhaust Flange Low File Bow S' Bore Exhaust Flange Long Radiation Of Pipe with Glasswood (254mm min thickness) Exhaust Flange As per layout with 2 SWG MS		yal Bolt	10 no.		Pcs			10
Cable Laying Charge Cable laying & termination of 185 rm Earthing System 100 feet Garthing Boring 38 mm Earthing Copper Lead 2 SWG for Boring & Termination Earthing Block / Equipotential bar 100 feet Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG for Boring & Termination Earthing Copper Lead 2 SWG mare Barthing Copper bar to gen & equipment for 250kva Exhaust Suggest Switch 3 Sper Boring Switchenss 3-4mm Exhaust Bends / Elbow 4 Insulation Of Pipe with Glasswool (25.4mm Exhaust Bends / Elbow 5 Dorn Material: Oopper, Surface-Electro Tinned Exhaust Bends / Elbow 4 Insulation Of Pipe with Glasswool (25.4mm min thickness) Exhaust Bends / Elbow 4 Insulation Of Pipe with Glasswool (25.4mm min thickness) Exhaust Bends / Elbow 4 Sper Insulation Of Pipe with Glasswool (25.4mm min thickness) <	_	yal Boit ble Tie	L-10"		Pack	* °	T	1
Earthing System 100 feet 10	_	blo Laving Chargo	Cable laving 8 termination of 100 cm		2 .	; 5	1	707
Earthing Boring 38 mm Earthing Boring 25WG for Boring & Termination Earthing Block / Equipotential bar facility Earthing Copper Lead 2 SWG for Boring & Termination Earthing Block / Equipotential bar facility Earthing Cable 2 SWG for Boring & Termination Earth cable lugs 10mension (LXWXD)mm - 250X40mmX5mm with connection facility Exhaust System: 10mension (LXWXD)mm - 250Xva Earth cable lugs 50mm2 BYA[Green] from Earthing Copper bar to gen & equipment for 250Xva Exhaust Silencer straight Pipe 10mension (LXWXD)mm - 250Xva Exhaust Flange 10mension (LXWXD)mm - 250Xva Exhaust Flange 10mension (LXWXD)mm - 250Xva Exhaust Silencer straight Pipe 10mension (LXWXD)mm - 250Xva Exhaust Silencer straight Pipe 10mension (LXWXD)mm - 250Xva Exhaust Flange 10mension (LXWXD)mm - 250Xva Exhaust Silencer straight Pipe 10mension (LXWXD)mm - 250X40mmX5mm with connection (LXWXD)mm - 250X40mm mith connection (LXWXD)m	1	ble Laying Charge	Cable laying & termination of 185 rm		3	Meter	eter 70	T
Earthing Copper Lead Earthing Block / Equipotential bar Earthing Block / Equipotential bar Earthing Cable Earth cable lugs Earth cable lugs Exhaust System: Exhaust Silencer straight Pipe Exhaust Flange Exhaust Bedds, Flange Exhaust Flange Exhaust Flange Exhaust Flange Exhaus	2 Ear	rtning System	100 foot			5	+	J
Earthing Copper Lead Earthing Block / Equipotential bar Earthing Cable Earthing Cable Earth cable lugs Earth cable lugs Exhaust System: Exhaust Silencer straight Pipe Exhaust Bends / Elbow Exhaust Fitting Cooling System: As per layout with 25 SWG Aluminium sheet clading. As per layout with 22 SWG MS sheet, Angle bar, flat bar support, Canvas cloth etc. Ducting area- DXW-2'X5'; RFT-15' Commissioning Material: Radiator coolant Lube oil Lube oil Battery electrolyte Diesel for Test Run (50% of Tank Capacity) Diesel for Test Run (50% of Tank Capacity) Client DG Foundation DG Room work with RCC foundation base. Client Client Client Client		Pipe	38 mm		Meter	er	er 14	\top
Earthing Block / Equipotential bar Facility Earthing Cable Earth cable lugs Earth cable lugs Exhaust System: Exhaust Sliencer straight Pipe Exhaust Sliencer straight Pipe Exhaust Flange Exhaust Flange Exhaust Flange Exhaust Flange Exhaust Flow E	2.4 Ear	thing Copper Lead	2 SWG for Boring & Termination		Meter	.er	:er 68	68
Earth cable lugs Earth cable lugs Exhaust System: Exhaust Slencer straight Pipe Exhaust Slencer straight Pipe Exhaust Slencer straight Pipe Exhaust Flange Exhaust Flange Exhaust Fitting Cooling System: Radiator Ducting Commissioning Material: Radiator coolant Lube oil Lube oil Battery electrolyte DG on Site Delivery Loading /Unloading/Lufting DG Foundation DG Foundation DG Room work with RCC foundation base. Client Client Client DG Foundation DG Room work with RCC foundation base. Client Client Client	2.5 Ear	rhting Block / Equipotential bar	Dimension (LXWXD)mm - 250X40mmX5mm with connection facility	ā	Pcs	"	5 2	
Earth cable lugs Exhaust System: Exhaust Slencer straight Pipe Exhaust Slencer straight Pipe Exhaust Bends /Elbow Exhaust Bends /Elbow Exhaust Flange Exhaust Flanges Exhaust F	2.6 Ear	rthing Cable	1X50 mm2 BYA(Green) from Earthing Copper bar to gen & equipment for 250kya		Meter		5	
Exhaust System: Exhaust Silencer straight Pipe Exhaust Silencer straight Pipe Exhaust Bends / Elbow Loding radius 90 deg L bow 5" bore Exhaust Bends / Elbow Welding neck flange 5" dia Insulation Of Pipe with Glasswool (25.4mm min thickness) All bracket, support must be made with MS angle 50X50X 4, 5 Exhaust Fitting Cooling System: As per layout with 22 SWG MS sheet, Angle bar, flat bar support, Canvas cloth etc. Ducting area- DXW-2'X5'; RFT-15' Commissioning Material: Radiator coolant Lube oil Battery electrolyte Fuel DG on Site Delivery Loading / Unloading / Lifting Civil Work DG Room work with RCC foundation base. Client Discenting - 1 YMANYC" Client Client Client	2.7 Ear	rth cable lugs	50 rm ,Material -Copper , Surface-Electro Tinned		Pcs		6	6 33
Exhaust Silencer straight Pipe Exhaust Bends / Elbow Exhaust Bends / Elbow Exhaust Bends / Elbow Exhaust Flange Exhaust F	3 Ex	haust System:						
Exhaust Bends / Elbow Exhaust Flange Insulation Of Pipe with Glasswool (25.4mm min thickness) All bracket, support must be made with MS angle 50X50X 4, 5 & 6 MM Cooling System: As per layout with 22 SWG MS sheet, Angle bar, flat bar support, Canvas cloth etc. Ducting area-DXW-2'XS'; RFT-15' Commissioning Material: Havoline Premix Coolent Lube oil Battery electrolyte Diesel for Test Run (50% of Tank Capacity) Diesel for Test Run (50% of Tank Capacity) Cilent DG Foundation DG Foundation DG Room work with RCC foundation base. Client Client Client	\perp	naust Silencer straight Pipe	MS Pipe bore 5", thickness 3-4mm		Meter			5 3
Exhaust Heat Insulation Exhaust Heat Insulation Exhaust Heat Insulation Exhaust Heat Insulation Insulation Of Pipe with Glasswool (25.4mm min thickness) along with 26 SWG Aluminium sheet clading. Exhaust Fitting Exhaust Fitting Exhaust Fitting Exhaust Fitting All bracket, support must be made with MS angle 50X50X 4, 5 & 6 MM Cooling System: As per layout with 22 SWG MS sheet, Angle bar, flat bar support, Canvas cloth etc. Ducting area-DXW-2'X5', RFF-15' Commissioning Material: Havoline Premix Coolent Lube oil Battery electrolyte DG on Site Delivery Loading /Unloading/Lifting Generator dry weight-2600 kg Civil Work DG Room work with RCC foundation base. Client Client Client	_	naust Bends / Elbow	Long radius 90 deg L bow 5" bore		Pcs		ω ω	1
Exhaust Heat Insulation All bracket Support must be made with MS angle 50X50X 4, 5	_	laustrialige	Insulation of Pine with Glasswool (25 Amm min thickness)		760		U	2 272
Exhasut Fitting All bracket, support must be made with MS angle 50X50X 4, 5 & 6 MM Cooling System: Radiator Ducting Radiator Ducting Radiator Ducting As per layout with 22 SWG MS sheet, Angle bar, flat bar support, Canvas cloth etc. Ducting area-DXW-2'X5'; RFT-15' Commissioning Material: Havoline Premix Coolent Lube oil Lube oil Battery electrolyte Specific gravity 1.250 Fuel DG on Site Delivery Loading/Unloading/Lifting Generator dry weight-2600 kg Civil Work DG Room work with RCC foundation base. Client Client Client	3.4 Exh	haust Heat Insulation	along with 26 SWG Aluminium sheet clading.		Job		1	1 7,604
Cooling System: As per layout with 22 SWG MS sheet, Angle bar, flat bar support, Canvas cloth etc. Ducting area- DXW-2'X5', RFT-15' Commissioning Material: Radiator coolant Lube oil Battery electrolyte Battery electrolyte Fuel DG on Site Delivery Loading /Unloading/Uffing Civil Work DG Foundation DG Generator dry weight-2600 Kg Client DG Generator DG Room work with RCC foundation base. Client DG Generator DG Room work with RCC foundation base. Client Client	3.5 Exh	hasut Fitting	All bracket , support must be made with MS angle 50X50X . & 6 MM	4, 5	Job		1	1 5,867
Radiator Ducting As per layout with 22 SWG MS sheet, Angle bar, flat bar support, Canvas cloth etc. Ducting area- DXW-2'X5'; RFT-15' Commissioning Material: Radiator coolant Lube oil Lube oil Battery electrolyte Specific gravity 1.250 Fuel DG on Site Delivery Loading/Unloading/Lifting Civil Work DG Foundation DG Foom work with RCC foundation base. Client DG Generator Dryners and with Park Capacity Client DG Generator DG Room work with RCC foundation base. Client Client Client Client	4 Co	oling System:						
Commissioning Material: Radiator coolant Radiator coolant Lube oil Battery electrolyte Fuel Fuel DG on Site Delivery Loading/Unloading/Lifting Civil Work DG Foundation	4.1 Ra	diator Ducting	As per layout with 22 SWG MS sheet,Angle bar, flat bar support,Canvas cloth etc. Ducting area- DXW-2'X5', RFT-15		Sq-ft		N/A	N/A 262
Radiator coolant Havoline Premix Coolent Lube oil S.R. 15 W 40 Battery electrolyte Specific gravity 1.250 Fuel Diesel for Test Run (50% of Tank Capacity) Client DG on Site Delivery Loading/Unloading/Lifting Generator dry weight-2600 kg Civil Work GRoom work with RCC foundation base. DG Foundation DG Room work with RCC foundation base. Client	5 Co	mmissioning Material:						
Lube oil SAE 15 W 40 Battery electrolyte Specific gravity 1.250 Fuel Specific gravity 1.250 Diesel for Test Run (50% of Tank Capacity) Client DG on Site Delivery Section Site Delivery Cooling / Unloading /		diator coolant	Havoline Premix Coolent		Liter			30
Battery electrolyte Specific gravity 1.250 Fuel Diesel for Test Run (50% of Tank Capacity) Client DG on Site Delivery Loading /Unloading/Lifting Generator dry weight-2600 Kg Civil Work DG Foundation DG Foundatio	5.2 Lul	be oil	SAE 15 W 40		Liter	er	er 40	40
Diesel for Test Run (50% of Tank Capacity) Client		ttery electrolyte	Specific gravity 1.250		Liter	P		20
DG on Site Delivery Loading /Unloading/Lifting Generator dry weight-2600 Kg Civil Work DG Room work with RCC foundation base. Client		el	Diesel for Test Run (50% of Tank Capacity)	Client	Liter	P	(4)	300
Loading/Unloading/Lifting Generator dry weight-2600 kg Civil Work DG Room work with RCC foundation base. DG Foundation Dimension LYWYD: 179/10/VC" Client	6 D0	3 on Site Delivery						
CIVII WORK DG Room work with RCC foundation base. DG Foundation	-	pading /Unloading/Lifting	Generator dry weight-2600 Kg		Job		1	1
DG Foundation DG Room work with RCC foundation base. Client	7 Civ	vil Work				1		
	7.1 DG	Foundation	DG Room work with RCC foundation base. Dimension- LXWXD: 17'X10'X6"	Client	Job		<u></u>	1

